



serie
UR-01



UNIÓN UNIVERSAL AUTOBLOCANTE
SELF-LOCKING UNIVERSAL COUPLING



REF.	Ø MIN.	Ø MAX.	L1	L2
UR-01-DN050	46	70	240	187
UR-01-DN065	70	95	240	212
UR-01-DN080	88	123	250	240
UR-01-DN100	108	143	250	260
UR-01-DN125	133	168	260	285
UR-01-DN150	159	194	260	311
UR-01-DN200	200	235	295	370
UR-01-DN250	250	285	305	420
UR-01-DN300	315	350	315	485

- Adecuado para unir todo tipo de tubos de presión tales como fundición, acero, PVC, fibrocemento, polietileno, etc.
- Bloqueo mecánico mediante mordientes metálicos para evitar el movimiento axial de la tubería.
- Amarre independiente en ambos lados.
- La desviación angular máxima permitida es de 10°.
- Presión de trabajo:
 - PN-16: de DN50 a DN200.
 - PN-10: DN250 y DN300.
- Fundición nodular GGG-50.
- Revestimiento EPOXI de 250µ de media.
- Tornillería con recubrimiento GEOMET y juntas de goma EPDM.

- Suitable for joining pipes of different materials, such as cast iron, stainless steel, PVC, asbestos cement, polythene and so on.
- Mechanical locking by means of metal inserts in order to avoid pipe's axial movement.
- Independent clamping on both sides.
- The maximum angular deviation permitted is 10°.
- Operating pressure:
 - PN-16: from DN50 to DN200.
 - PN-10: DN250 and DN300.
- GGG-50 nodular cast iron.
- 250µ EPOXY coating on average.
- Equipped with GEOMET coated bolts AISI, nuts and washers, and EPDM rubber seals.

UR-cast
Water Fittings

www.ur-cast.com
Tfno: (+34) 945 200 466 - Fax: (+34) 945 249 867
C/ Urartea nº 15-17, pab. 6-10, P. I. ALI GOBEO / 01010 VITORIA-GASTEIZ / ÁLAVA (Spain)