



serie
UR-34



**COLLARÍN DE TOMA PARA
TUBO DE FUNDICIÓN DÚCTIL**

INTAKE RING FOR DUCTILE IRON PIPES



REF.	DN tubo Pipe DN	Salida Outlet	L1	L2	L3
UR-34-DN100-112	DN-100	1 1/2"	205	177	160
UR-34-DN100-200	DN-100	2"	205	177	160
UR-34-DN150-112	DN-150	1 1/2"	275	230	210
UR-34-DN150-200	DN-150	2"	275	230	210
UR-34-DN200-112	DN-200	1 1/2"	330	283	270
UR-34-DN200-200	DN-200	2"	330	283	270

- Presión de trabajo PN-16.
- Fundición nodular GGG-50.
- Revestimiento EPOXI de 250 μ de media.
- Tornillería GEOMET y juntas de goma EPDM.

- *PN-16 operating pressure.*
- *GGG-50 nodular cast iron.*
- *250 μ EPOXY average coating.*
- *Equipped with GEOMET coated bolts, nuts and washers, and EPDM rubber seals.*

UR-cast^o
Water Fittings

www.ur-cast.com

Tfno: (+34) 945 200 466 - Fax: (+34) 945 249 867

C/ Urartea nº 15-17, pab. 6-10, P. I. ALI GOBEO / 01010 VITORIA-GASTEIZ / ÁLAVA (Spain)