



serie
UR-05



UNIÓN GIBALT PARA TUBERÍAS DE PVC Y PVC ORIENTADO

GIBALT COUPLING
FOR PVC AND PVC-O PIPES



REF.	Ø	L1	L2
UR-05-DE050	50	122	120
UR-05-DE063	63	142	137
UR-05-DE075	75	146	149
UR-05-DE090	90	146	164
UR-05-DE110	110	166	184
UR-05-DE125	125	166	199
UR-05-DE140	140	166	214
UR-05-DE160	160	206	234
UR-05-DE180	180	206	254
UR-05-DE200	200	208	274
UR-05-DE250	250	232	341
UR-05-DE315	315	232	406
UR-05-DE400	400	234	495
UR-05-DE500	500	234	596
UR-05-DE630	630	250	745
UR-05-DE710	710	250	825
UR-05-DE800	800	250	915

- Amplia gama de diámetros que cubre tubos desde 50 hasta 800 milímetros.
- Presión de trabajo PN-16.
- Fundición nodular GGG-50.
- Revestimiento medio de EPOXI de 250 μ .
- Tornillería bicromatada y juntas de goma EPDM.
- Válido para tubos de PVC orientado.

- Wide range of diameters covering pipes from 50 to 800 millimeters.
- PN-16 operating pressure.
- GGG-50 nodular cast iron.
- 250 μ EPOXY average coating.
- Equipped with bichromate bolts and EPDM rubber seals.
- Suitable for PVC-O pipes.

UR-cast^o
Water Fittings

www.ur-cast.com

Tfno: (+34) 945 200 466 - Fax: (+34) 945 249 867

C/ Urartea nº 15-17, pab. 6-10, P. I. ALI GOBEO / 01010 VITORIA-GASTEIZ / ÁLAVA (Spain)